



Technical Data Sheet

3, 5-Xylidine

1- Introduction

3, 5-Xylidine is a yellow to reddish brown coloured, clear liquid. It is insoluble in water and soluble in ether, acetone ≥ 100 mg/ml at 18 °C (RAD). It is stable under recommended storage conditions. It is sensitive to air and light and tend to darken on storage. Avoid contact with skin and eyes.

Product Name: - 3, 5-Xylidine

Synonyms: - 3, 5-Dimethylaniline; 3, 5-Dimethylbenzeneamine; 1-Amino-3, 5-Dimethylbenzene; 5-Amino-m-xylene; 5-Amino-1,3-xylene


CAS No. 108-69-0

UN No. 1711

EINECS# 203-607-0

Mol. Formula :- $(\text{CH}_3)_2\text{C}_6\text{H}_3\text{NH}_2$

Mol. Structure:-



Mol. Weight: - 121.18



2- Physical Properties:

Sr. No.	Properties	3, 5-Xylidine
1-	Appearance	Clear liquid
2-	Colour	Yellow to reddish brown liquid.
3-	Odour	Characteristic aromatic odour.
4-	pH(1%Solution)	Not applicable
5-	Boiling Point/range	220 °C – 221 °C.
6-	Melting point	9.8 °C.
6-	Flash Point	93 °C (201 °F)
7-	Auto ignition temperature	590 °C (1,094 °F)
8-	Vapor Pressure	1.29 hPa (0.97 mmHg) at 20 °C (68 °F)
9-	Density	0.970 g/cm ³
10-	Solubility water	Water :<1 mg/ml at 18 °C (RAD), Soluble in ether, Acetone:>=100 mg/ml at 18 °C (RAD).
11-	Decomposition	Decomposes on heating producing toxic fumes Carbon oxides, nitrogen oxides (NO _x).



3. Product Quality Specification:

Sr. No.	Test Parameter	Specification
1-	Appearance	Clear, colorless to amber colored liquid.
2-	Moisture (by KF)	0.5 % Max.
3-	Purity (by GC)	99 % Min.

4. Packing Information:

Sr. Number	Grade	Packing	Secondary Packing
1-	200 Kg capacity MS drum/ Tanker	200 kg of 3, 5-Xylidine packed in MS drum or in tanker.	-----

DNL can customize packing for different quantities.

5. PRODUCT USES:

3, 5-Xylidine is widely used as raw materials to produce imaging chemicals like pigments and dyestuffs. All of these compounds are also used in the production of antioxidants, agricultural, pharmaceutical, rubber chemicals and other target organic molecules.



6. Regulatory Information:-

Particulars	Information	Pictogram
Hazard Class	6.1	
Label	Toxic	
Subsidiary Label	Warning	
UN Number	1711	
Proper shipping Name	3, 5-Xylidine	
Packing Group	II	

RTECS#:ZE9625000

7. PRODUCT SAFETY INFORMATION:

3, 5-Xylidine may be fatal if inhaled. May cause respiratory tract irritation, skin toxic if absorbed through skin. It may cause skin irritation & may be harmful if swallowed. It is stable under recommended storage conditions. Materials keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. Materials keep away from acids, Acid chlorides, Acid anhydrides, Oxidizing agents, Chloroformates, Halogens. Hazardous decomposition products formed under fire conditions. - Carbon oxides, nitrogen oxides (NO_x). As with any chemical, 3, 5-Xylidine requires care in handling. Anyone responsible for the procurement, use or disposal of this product should familiarize himself and those handling the product with the appropriate safety and handling precautions. This information is available in the Material Safety Data Sheet, which may be obtained by contacting our representative.



8. Manufacture Site:

Deepak Nitrite Limited (APL Division)
Plot No. 1 to 6, 26 to 31, MIDC Industrial Area, Dhatav, Roha,
Dist. Raigad 402 116, Maharashtra.
Phone No. 02194 263550/263750

9. Corporate Headquarter:

Deepak Nitrite Ltd.
Aaditya-I, National Highway No. 8, Chhani Road,
Vadodara - 390 024,
India
Ph. No (0265) 2765200

10. For Chemical Emergency:

Spill, Leak, Fire, Exposure, or Accident, Call CHEMTREC
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-527-3887



Disclaimer:

The information published in this Technical Data Sheet has been compiled with the basic objective of selling and use of 3, 5-Xylidine that meet basic quality requirements. Information presented herein has been considered to be accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. The information is provided without any representation of warranty, expressed or implied, regarding the accuracy or correctness. It is the user's responsibility to determine the accuracy or suitability of this information. Deepak Nitrite assume no responsibility for the accuracy or suitability of such information for application to the purchaser's intended purpose or for consequences of it's use. Adoption of necessary safety precautions, for any intended usage, shall remain the user's responsibility.

Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment. Deepak Nitrite assumes no responsibility for injury to user or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the Material Safety Data Sheet. Additionally, Deepak Nitrite assumes no responsibility for injury to user or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. The conditions or methods of handling, storage, and / or use of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, and / or use of this product.

All information provided herein is intended for use by persons having requisite knowledge, skill and experience in the chemical industry.

Deepak Nitrite Ltd

